



Terminal No.	Pin Name
1	VSS
2	VDD
3	V0
4	/WR
5	/RD
6	/CS
7	A1
8	/RESET
9	D0
10	D1
11	D2
12	D3
13	D4
14	D5
15	D6
16	D7
17	NC
18	VOUT
19	BLA
20	BLK




Pixels Details
Scale=30/1



Wiring Details(Top View)
Scale=Free

Note:

- *1. Display Type : FSTN, Positive, Transmissive
- *2. Viewing Direction : 6H
- *3. Duty : 1/240, Bias : 1/14
- *4. Backlight Color : White
- *5. Backlight Supply : 170mA(3.3V TYP.)
- *6. Operating Voltage : 3.3V
- *7. Operating Temperature : -20°C~70°C
- *8. Storage Temperature : -30°C~80°C
- *9. Controller : T8000 or equivalent
- *10. An external VR(25K to 50K) must be connected for Contrast Control



Backlight Circuit
(No. of LEDs = 10pcs)
Scale=free

C		
B		
A		
Rev	Note	Date
Dwg Title LM320240TCW Outline Dwg		
Dwg No.	MK-002436-1-1	Date 2008-05-10
Scale 6/5	Tol. ±0.5	Unit mm Paper Size A3
Approved	Checked	Drawn Zhou Huifang

TOPWAY