



K1 Terminal		
No.	Name	(*)10
1	VSS	
2	VDD	
3	V0	
4	/WR	
5	/RD	
6	/CS	
7	RS	
8	/RST	
9	DB0	
10	DB1	
11	DB2	
12	DB3	
13	DB4	
14	DB5	
15	DB6	
16	DB7	
17	BUSY	
18	VDOUT	
19	BLA	
20	BLK	

Note:

- *1. Display Type : STN, Negative, Transmissive
- *2. Viewing Direction : 6H
- *3. Duty : 1/240
- *4. Backlight Color : White
- *5. Backlight Supply : 5.0V
- *6. Operating Voltage : 5.0V
- *7. Operating Temperature : -20°C~70°C
- *8. Storage Temperature : -30°C~80°C
- *9. Controller : RA8806 or equivalent
- *10. An external VR(25K to 50K) must be connected for Contrast Control
- *11. Environmental Safe Standard : RoHS

C			
B			
A	Typing Correction		Cheng Yuanyuan 2009-05-12
Rev	Note		Date
Dwg Title LM2088RFW outline Dwg			
Dwg No.	MK-002817a-1-1		Date 2009-04-09
Scale	1/1	Tol.	±0.5
Unit	mm	Paper Size	A3
Approved		Checked	Drawn Zhou Huifang

TOPWAY