



| K1 Terminal | |
|-------------|-------------|
| No | Pin Name |
| 1 | LED_CATHODE |
| 2 | LED_CATHODE |
| 3 | LED_ANODE |
| 4 | LED_ANODE |
| 5 | NC |
| 6 | NC |
| 7 | NC |
| 8 | /RST |
| 9 | /SPEN |
| 10 | SPCK |
| 11 | SPDA |
| 12 | D0 |
| : | : |
| 35 | D23 |
| 36 | HSYNC |
| 37 | VSYNC |
| 38 | DCLK |
| 39 | NC |
| 40 | NC |
| 41 | VDD |
| 42 | VDD |
| 43 | NC |
| : | : |
| 51 | NC |
| 52 | DEN |
| 53 | GND |
| 54 | GND |

Note:

- *1. LCD Display Type: TFT, Transmissive
- *2. Pixel Arrangement: RGB-SPRIPE
- *3. Operating Voltage : 3.3V
- *4. Viewing Direction : 12H
- *5. Backlight Supply : 20mA (19.2V TYP.)
- *6. Backlight : LEDs
- *7. Operating Temperature : -20°C~70°C
- *8. Storage Temperature : -30°C~80°C

| | | |
|----------|-------------------------|------------------------|
| C | | |
| B | | |
| A | Refine Outline | Yang 2012-01-31 |
| Rev | Note | Date |
| Dwg | Title | |
| | LMT035KDH03 Outline Dwg | |
| Dwg No. | MK-003085a-1-1 | Date 2009-09-25 |
| Scale | Tol. | Unit |
| 1/1 | ±0.5 | mm |
| Approved | Checked | Paper Size A3 |
| | | Drawn ChengYuanyuan |

TOPWAY