



#A Backside

K1 Terminal	
No	Pin Name
1	RX3+
2	RX3-
3	NC
4	FRC
5	GND
6	RXC+
7	RXC-
8	GND
9	RX2+
10	RX2-
11	GND
12	RX1+
13	RX1-
14	GND
15	RX0+
16	RX0-
17	LR
18	UD
19	VCC_IN
20	VCC_IN

K2 Terminal	
No	Pin Name
1	BL_Vi
2	BL_ADJ
3	BL_EN
4	BL_GND

Note:

- *1. LCD Display Type: TFT.Transmissive
- *2. Pixel Arrangement: RGB-SPRIPE
- *3. Operating Voltage : 3.3V
- *4. Backlight Supply : 12.0V
- *5. Backlight : White LED
- *6. K1: STARCONN 076B20-0048RA-G4 or equivalent
- *7. K2: LM123S004HTF13, 4PIN, UNE or equivalent
- *8. Operating Temperature : -20°C~70°C
- *9. Storage Temperature : -30°C~80°C

C				
B				
A	Revise Outline			Yang 2011-06-10 Date
Rev	Note			Date
Dwg	Title	LMT070DICFWD-NDN Outline Dwg		
Dwg No.	MK-003644a-1-1			Date 2011-05-25
Scale	1/1	Tol.	±0.5	Unit mm Paper Size A3
Approved		Checked		Drawn Yang Lin

TOPWAY