



Terminal (K1)			
Name	No	No	Name
VDD_BL	2	1	VDD_BL
VDD	4	3	VDD
VSS	6	5	VSS
/RD	8	7	/WR
RS	10	9	/CS
D14	12	11	D15
D12	14	13	D13
D10	16	15	D11
D8	18	17	D9
D6	20	19	D7
D4	22	21	D5
D2	24	23	D3
D0	26	25	D1
VSS	28	27	VSS
NC	30	29	NC
NC	32	31	NC
NC	34	33	NC
△ NC	36	35	NC △

- Note:
- *1. LCD Display Type: TFT, Transmissive
 - *2. Pixel Arrangement: RGB-SPRIPE
 - *3. Color Depth: 65k colors
 - *4. Logic Supply: 3.3V
 - *5. Backlight Supply: 5.0V
 - *6. Backlight: LEDs
 - *7. Operating Temperature: -20°C~70°C
 - *8. Storage Temperature: -30°C~80°C
 - *9. Environmental Standard: ROHS

C		
B		
A	Typing Correction	K.C. 2011-09-26
Rev	Note	Date
Dwg Title	LMT070DICFWD-NBN Outline Dwg	
Dwg No.	MK-003755a-1-1	Date 2011-01-12
Scale	Tol.	Unit
1/1	±0.5	mm
Approved	Checked	Paper Size A3
		Drawn Yang Lin

TOPWAY