


K1 Terminal	
No	Pin Name
1	NC
2	NC
3	NC
4	NC
5	GND
6	VCOM
7	VCC
8	MODE
9	DE
10	VS
11	HS
12	B7
:	:
19	B0
20	G7
:	:
27	G0
28	R7
:	:
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC

Note:

- *1. LCD Display Type: TFT.Transmissive
- *2. Pixel Arrangement: RGB-STRIPE
- *3. Operating Voltage : 3.3V
- *4. Backlight Supply : 180mA (9.6V Typ.)
- *5. Backlight : LEDs
- *6. Color Depth : 16M colors
- *7. K2 Connector Type : 35001-HS-02 or equivalent
- *8. Operating Temperature : -20°C~70°C
- *9. Storage Temperature : -30°C~80°C



K1 Terminals Details
(Conductor Side)
Scale=3/2

C		
B	Refine Dwg	Yang 2012-05-03
A	Refine Dwg	Yang 2011-12-21
Rev	Note	Date
Dwg Title LMT080DIEFWU-NNA Outline Dwg		
Dwg No.	MK-003834b-1-1	Date 2012-04-25
Scale	Tol.	Unit
4/5	±0.5	mm
Approved	Checked	Paper Size A3
		Drawn Yang Lin
TOPWAY		