



K1 Terminals Details  
(Conductor Side)  
Scale=3/2

K1 Terminal	
No	Pin Name
1	NC
2	NC
3	NC
4	NC
5	GND
6	VCOM
7	VCC
8	MODE
9	DE
10	VS
11	HS
12	B7
:	:
19	B0
20	G7
:	:
27	G0
28	R7
:	:
35	R0
36	GND
37	DCLK
38	GND
39	L/R
40	U/D
41	VGH
42	VGL
43	AVDD
44	RESET
45	NC
46	VCOM
47	DITHB
48	GND
49	NC
50	NC

- Note:
- \*1. LCD Display Type: TFT.Transmissive
  - \*2. Pixel Arrangement: RGB-SPRIPE
  - \*3. Operating Voltage : 3.3V
  - \*4. Backlight Supply : 9.6V Typ.
  - \*5. Backlight : LEDs
  - \*6. Color Depth : 16M colors
  - \*7. K2 Connector Type : 35001-HS-02 or equivalent
  - \*8. Operating Temperature : -20°C~70°C
  - \*9. Storage Temperature : -30°C~80°C

C		
B		
A		
Rev/Note		Date
Dwg Title	LMT080DIEFWU Outline Dwg	
Dwg No.	MK-003973-1-1	Date 2012-04-25
Scale 4/5	Tol. ±0.5	Unit mm Paper Size A3
Approved	Checked	Drawn Yang Lin
<b>TOPWAY</b>		