



深圳市拓普微科技开发有限公司

SHENZHEN TOPWAY TECHNOLOGY CO., LTD.

LMT050ENCFWU

LCD Module User Manual

Prepared by: Gonghuimei Date: 2021-07-26	Checked by: Date:	Approved by: Date:
---	----------------------------------	-----------------------------------

Rev.	Descriptions	Release Date
0.1	Preliminary release	2021-07-26

Table of Content

1. General Specification.....	3
2. Block Diagram.....	3
3. Input/Output Terminals.....	4
4. Absolute Maximum Ratings.....	5
5. Electrical Characteristics.....	5
5.1 DC Characteristics.....	5
5.2 LED Backlight Circuit Characteristics.....	5
5.3 Power ON/OFF Sequence.....	6
6. AC Characteristics.....	7
6.1 Timing Characteristics.....	7
6.2 Input Clock and Data Timing Diagram.....	7
6.3 Data Input Format.....	8
7. Optical Characteristics.....	9
8. LCD Module Design and Handling Precautions.....	11

1. General Specification

Screen Size(Diagonal) :	5.0"
Active Area :	108.0 x 64.8 (mm)
Number of dots :	800 (RGB) x 480
Pixel Pitch :	0.135x 0.135 (mm)
Color Depth :	16.7M colors
Display Technology :	a-Si TFT active matrix
Display Mode :	Normal White, Transmissive
Display Interface :	RGB
Viewing Direction :	6 o'clock(Gray scale Inversion) (*1) 12 o'clock (*2)
Surface Treatment :	Anti-Glare Treatment
Operating Temperature :	-30 ~ +85°C
Storage Temperature :	-40 ~ +90°C


Note:

*1. For saturated color display content (eg. pure-red, pure-green, pure-blue or pure-colors-combinations).

*2. For “color scales” display content.

*3. Color tone may slightly change by temperature and driving condition.

2. Block Diagram



3. Input/Output Terminals

Pin No.	Pin Name	I/O	Descriptions
1	NC	-	No connection
2	NC	-	No connection
3	GND	P	Ground
4	VDD	P	Power supply
5	R0		Data input
:	:		
12	R7		
13	G0		Data input
:	:		
20	G7		
21	B0		Data input
:	:		
28	B7		
29	GND	P	Ground
30	CLKIN		Clock for input data. Data latched at falling edge of this signal.
31	STBYB		Standby mode. STBYB="1": Normally operation. STBYB="0": Standby mode .
32	HSD		Horizontal sync input.
33	VSD		Vertical sync input
34	DEN		Data input enable(unnecessary)
35	NC	--	No connection
36	GND	P	Ground
37	LED_A		LED Anode(+)
38	LED_K1		LED Cathod(-)
39	LED_K2		LED Cathod(-)
40	LED_K3		LED Cathod(-)

Note:

* 1: Please add the FPC connector type and matched one if necessary.

* 2: I——Input, O——Output, P——Power/Ground

4. Absolute Maximum Ratings

Items	Symbol	Min.	Max.	Unit	Remark
Power voltage	VDD	-0.5	4.5	V	Note1
Input voltage	V _{IN}	-0.5	5.0	V	
Operating Temperature	T _{OP}	-30	85	°C	
Storage Temperature	T _{ST}	-40	90	°C	
Relative Humidity Note2	RH	--	≤95	%	Ta≤40°C
		--	≤85	%	40°C < Ta ≤ 50°C
		--	≤55	%	50°C < Ta ≤ 60°C
		--	≤36	%	60°C < Ta ≤ 70°C
		--	≤24	%	70°C < Ta ≤ 80°C
Absolute Humidity	AH	--	≤70	g/m ³	Ta > 70°C

Note:

- *1. This rating applies to all parts of the module. And should not be exceeded.
- *2. Input voltage include R0~R5, G0~G5, B0~B5, User should set input voltage on recommend value.
- *3. Ta means the ambient temperature. It is necessary to limit the relative humidity to Condensation on the module is not allowed.
- *4. Ambient temperature when the backlight is lit (reference value)
- *5. Any Stresses exceeding the Absolute Maximum Ratings may cause substantial damage to the device. Functional operation of this device at other conditions beyond those listed in the specification is not implied and prolonged exposure to extreme conditions may affect device reliability.

5. Electrical Characteristics

5.1 DC Characteristics

GND=0V, Ta = 25°C

Items		Symbol	Min.	Typ.	Max.	Unit	Remark
Power voltage		VDD	3.0	3.3	3.6	V	
Input signal voltage	Low Level	V _{IL}	0	--	0.3xVDD	V	
	High Level	V _{IH}	0.7xVDD	--	VDD	V	
Output signal voltage	Low Level	V _{OL}	--	--	GND+0.4	V	
	High Level	V _{OH}	VDD-0.4	--	--	V	
Operating Current (*1)	I _{DD}	-	TBD	-	mA	All black	

Note:


- *1. For different LCM, the value may have a bit of difference. To test the current dissipation, use "all Black Pattern".

5.2 LED Backlight Circuit Characteristics

Items	Symbol	MIN.	TYP.	MAX.	Unit	Note
Forward Voltage	V _F	-	9.3	9.9	V	
Forward Current	I _F	-	175	-	mA	Note1
Backlight Power Consumption	W _{8L}	-	1628		mW	
Life Time	-	50000	-	-	Hrs	Note3


Note:

- *1. The LED driving condition is defined for each LED module (3 LED Serial, 6 LED Parallel), and which depend on Forward Current setting.
- *2. Under LCM operating, a constant forward current should be used. And forward voltage is for reference only.
- *3. I_F is defined for one channel LED. Optical performance should be evaluated at Ta=25°C only if LED is driven by high current, high ambient temperature & Humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.
- *4. The LED driving condition is defined for each LED module




No. of LED = $6 \times 3 = 18$ pcs

5.3 Power ON/OFF Sequence



Power On Sequence




Power Off Sequence

6. AC Characteristics

6.1 Timing Characteristics


Item	Symbol	MIN.	TYP.	MAX.	Unit	Remark
HS setup time	T_{hst}	8	-	-	ns	
HS hold time	T_{hhd}	8	-	-	ns	
VS setup time	T_{vst}	8	-	-	ns	
VS hold time	T_{vhd}	8	-	-	ns	
Data setup time	T_{dsu}	8	-	-	ns	
Data hole time	T_{dhd}	8	-	-	ns	
DE setup time	T_{esu}	8	-	-	ns	
DE hold time	T_{ehd}	8	-	-	ns	
CLKIN cycle time	T_{cph}	20	-	-	ns	
CLKIN pulse width	T_{cwh}	40	50	60	%	
VDD Power On Slew rate	T_{POR}	-	-	20	ms	

6.2 Input Clock and Data Timing Diagram




6.3 Data Input Format

Item	Symbol	MIN.	TYP.	MAX.	Unit
Horizontal Display Area	t_{hd}	800			CLKIN
CLKIN Frequency	f_{clk}	-	30	50	MHz
One Horizontal Line	t_h	889	928	1143	CLKIN
HSD pulse width	t_{hpw}	1	48	255	CLKIN
HSD Blanking	t_{hb}	88			CLKIN
HSD Front Porch	t_{hfp}	1	40	255	CLKIN
Vertical Display Area	t_{vd}	480			T_H
VSD period time	t_v	513	525	767	T_H
VSD pulse width	t_{vpw}	3	3	255	T_H
VSD Blanking	t_{vb}	32			T_H
VSD Front Porch	t_{vfp}	1	13	255	T_H



Horizontal input timing diagram



Vertical input timing diagram

7. Optical Characteristics

Item		Symbol	Condition	MIN.	TYP.	MAX.	UNIT	Note.
Viewing angle		θ_{T}	$(\text{CR} \geq 10)$	40	50	-	degree	Note 2,3
		θ_{B}		60	70	-		
		θ_{L}		60	70	-		
		θ_{R}		60	70	-		
Contrast ratio		CR	$\theta=0^{\circ}$	500	600	-	-	Note 3
Response Time		T_{on}	25°C	-	20	30	ms	Note 4
		T_{off}						
Chromaticity	White	X	Backlight is on	0.268	0.318	0.368		Note 1,5
		Y		0.302	0.352	0.402		
	Red	X		0.547	0.597	0.647		Note 1,5
		Y		0.298	0.348	0.398		
	Green	X		0.279	0.329	0.379		Note 1,5
		Y		0.553	0.603	0.653		
	Blue	X		0.101	0.151	0.201		Note 1,5
		Y		0.065	0.115	0.165		
Uniformity		U		75	80	--	%	Note 6
NTSC				45	50		%	Note 5
Luminance		L		800	1000	--	cd/m^2	Note 7

Test Conditions:

1. IF= 175mA, VF=9.3V, and the ambient temperature is 25. $^\circ\text{C}$
2. The test systems refer to Note 1 and Note 2.

Note 1:

The data are measured after LEDs are turned on for 5 minutes. LCM displays full white. The brightness is the average value of 9 measured spots. Measurement equipment SR-3A (1°)


Measuring condition:

- Measuring surroundings: Dark room
- Measuring temperature: Ta=25°C.
- Adjust operating voltage to get optimum contrast at the center of the display.

Note 2:

The definition of viewing angle:

Refer to the graph below marked by θ and ϕ



Note 3:

The definition of contrast ratio (Test LCM using SR-3A (1°)):

$$\text{Contrast Ratio (CR)} = \frac{\text{Luminance When LCD is at "White" state}}{\text{Luminance When LCD is at "Black" state}}$$


(Contrast Ratio is measured in optimum common electrode voltage)

Note 4:

Definition of Response time. (Test LCD using BM-7A(2°)):

The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively.

The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.




Note 5:

Definition of Color of CIE1931 Coordinate and NTSC Ratio.

Color gamut:

$$S = \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}} \times 100\%$$




Note 6:

The luminance uniformity is calculated by using following formula.

$$\Delta Bp = Bp (\text{Min.}) / Bp (\text{Max.}) \times 100 (\%)$$

Bp (Max.) = Maximum brightness in 9 measured spots

Bp (Min.) = Minimum brightness in 9 measured spots.



Note 7:

Measured the luminance of white state at center point

8. LCD Module Design and Handling Precautions

- Please ensure V0, VCOM is adjustable, to enable LCD module get the best contrast ratio under different temperatures, view angles and positions.
- Normally display quality should be judged under the best contrast ratio within viewable area. Unexpected display pattern may come out under abnormal contrast ratio.
- Never operate the LCD module exceed the absolute maximum ratings.
- Never apply signal to the LCD module without power supply.
- Keep signal line as short as possible to reduce external noise interference.
- IC chip (e.g. TAB or COG) is sensitive to light. Strong light might cause malfunction. Light sealing structure casing is recommended.
- Make sure there is enough space (with cushion) between case and LCD panel, to prevent external force passed on to the panel; otherwise that may cause damage to the LCD and degrade its display result.
- Avoid showing a display pattern on screen for a long time (continuous ON segment).
- LCD module reliability may be reduced by temperature shock.
- When storing and operating LCD module, avoids exposure to direct sunlight, high humidity, high or low temperature. They may damage or degrade the LCD module.
- Never leave LCD module in extreme condition (max./min storage/operate temperature) for more than 48hr.
- Recommend LCD module storage conditions is 0 C~40 C <80%RH.
- LCD module should be stored in the room without acid, alkali and harmful gas.
- Avoid dropping & violent shocking during transportation, and no excessive pressure press, moisture and sunlight.
- LCD module can be easily damaged by static electricity. Please maintain an optimum anti-static working environment to protect the LCD module. (eg. ground the soldering irons properly)
- Be sure to ground the body when handling LCD module.
- Only hold LCD module by its sides. Never hold LCD module by applying force on the heat seal or TAB.
- When soldering, control the temperature and duration avoid damaging the backlight guide or diffuser which might degrade the display result such as uneven display.
- Never let LCD module contact with corrosive liquids, which might cause damage to the backlight guide or the electric circuit of LCD module.
- Only clean LCD with a soft dry cloth, Isopropyl Alcohol or Ethyl Alcohol. Other solvents (e.g. water) may damage the LCD.
- Never add force to components of LCD module. It may cause invisible damage or degrade the module's reliability.
- When mounting LCD module, please make sure it is free from twisting, warping and bending.
- Do not add excessive force on surface of LCD, which may cause the display color change abnormally.
- LCD panel is made with glass. Any mechanical shock (e.g. dropping from high place) will damage the LCD module.

9. 液晶显示模块设计和使用须知



- 请注意 V0, VCOM 的设定, 以确保液晶显示模块在不同的使用温度下以及在不同的视角和位置观察模块显示, 均能达到最佳对比度, 请务必将应用电路上设置为对比度可调。
- 请注意液晶显示模块的显示品质判定是指在正常对比度下以及视窗(V. A)范围内进行的, 非正常对比度下液晶可能会出现非预期的显示不良, 应注意区分。
- 请勿在最大额定值以外使用液晶显示模块。
- 请勿在没有接通电源的条件下, 给液晶显示模块输送信号。
- 请尽可能缩短信号线的连接, 以避免对液晶显示模块的信号干扰。
- 集成电路因 IC 芯片(如 TAB 或 COG)对紫外线极为敏感, 强光环境下可能会引起液晶显示模块功能失效, 故应采用不透光的外壳。
- 请在液晶显示模块与外壳之间保留足够的空间(可使用衬垫), 以缓冲外力对液晶显示模块的损坏或因受力不均而产生的显示不匀等异常现象。
- 避免液晶显示屏在某一画面下长时间点亮, 否则有出现残影的风险; 请通过软件每隔一段时间改变一次画面。
- 液晶显示模块的可靠性可能因温度冲击而降低。
- 请勿在阳光直射、高湿、高温或低温下储存和使用液晶显示模块, 这将造成液晶显示模块的损坏或失效。
- 请勿在极限环境(最大/最小存储/工作温度)下使用或放置液晶显示模块超过 48 小时以上。
- 液晶显示模块建议存储条件为: 0 C~40 C <80%RH。
- 请勿让液晶显示模块存储于带有 酸性, 碱性, 有害气体环境之中。
- 在运输过程中, 请勿让液晶显示模块跌落与猛烈震动, 同时避免 异常挤压, 高湿度, 与阳光照射。
- 液晶显示模块极易受静电损坏, 请务必保证液晶显示模块在防静电的工作环境中使用或保存。(如: 烙铁正确接地, 等)
- 拿取液晶显示模块时需注意操作人员的接地情况。
- 请手持液晶显示模块的边沿取放模块, 防止热压纸或 TAB 部位受力。
- 焊接液晶模块时, 请注意控制烙铁的温度、焊接时间, 以免烫坏导光板或偏光片, 导致显示不匀等不良现象发生。
- 请勿使用洗板水等腐蚀性液体接触液晶模块, 以免腐蚀导光板或模块电路。
- 仅可使用柔软的干布, 异丙醇或乙醇清洁液晶屏表面, 其他任何溶剂(如: 水)都有可能损坏液晶模块。
- 请勿挤压液晶显示模块上的元器件, 以避免产生潜在的损坏或失效而影响产品可靠性。
- 装配液晶显示模块时, 请务必注意避免液晶显示模块的扭曲或变形。
- 请勿挤压液晶显示屏表面, 这将导致显示颜色的异常。
- 液晶屏由玻璃制作而成, 任何机械碰撞(如从高处跌落)均有可能损坏液晶显示模块。

- | | |
|---|---|
| <ul style="list-style-type: none">- Protective film is attached on LCD screen. Be careful when peeling off this protective film, since static electricity may be generated.- Polarizer on LCD gets scratched easily. If possible, do not remove LCD protective film until the last step of installation.- When peeling off protective film from LCD, static charge may cause abnormal display pattern. The symptom is normal, and it will turn back to normal in a short while.- LCD panel has sharp edges, please handle with care.- Never attempt to disassemble or rework LCD module.- If display panel is damaged and liquid crystal substance leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes promptly wash it off using soap and water.- | <ul style="list-style-type: none">- 液晶屏表面带有保护膜，揭除保护膜时需要注意可能产生的静电。- 因液晶显示屏表面的偏光片极易划伤，安装完成之前请尽量不要揭下保护膜。- 请缓慢揭除保护膜，在此过程中液晶显示屏上可能会产生静电，此为正常情况，可在短时间内消失。-- 请注意避免被液晶显示屏的边缘割伤。- 请不要试图拆卸或改造液晶显示模块。- 当液晶显示屏出现破裂，内部液晶液体可能流出；相关液体不可吞吃，绝对不可接触嘴巴，如接触到皮肤或衣服，请使用肥皂与清水彻底清洗。 |
|---|---|



Warranty

This product has been manufactured to our company's specifications as a part for use in your company's general electronic products. It is guaranteed to perform according to delivery specifications. For any other use apart from general electronic equipment, we cannot take responsibility if the product is used in medical devices, nuclear power control equipment, aerospace equipment, fire and security systems, or any other applications in which there is a direct risk to human life and where extremely high levels of reliability are required. If the product is to be used in any of the above applications, we will need to enter into a separate product liability agreement.


- We cannot accept responsibility for any defect, which may arise from additional manufacturing of the product (including disassembly and reassembly), after product delivery.
- We cannot accept responsibility for any defect, which may arise after the application of strong external force to the product.
- We cannot accept responsibility for any defect, which may arise due to the application of static electricity after the product has passed our company's acceptance inspection procedures.
- When the product is in CCFL models, CCFL service life and brightness will vary according to the performance of the inverter used, leaks, etc. We cannot accept responsibility for product performance, reliability, or defect, which may arise.
- We cannot accept responsibility for intellectual property of a third part, which may arise through the application of our product to our assembly with exception to those issues relating directly to the structure or method of manufacturing of our product.



DETAIL A
SCALE 100:1



DETAIL B
SCALE: 4:1



NO.	PIN NAME
1	NC
2	NC
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLKIN
31	STBYB
32	HSD
33	VSD
34	DEN
35	NC
36	GND
37	LED_A
38	LED_K1
39	LED_K2
40	LED_K3

Note:

- *1. LCD Display Type: TFT.Transmissive
- *2. Pixel Arrangement: RGB-STRIFE
- *3. Color Depth : 16.7M color
- *4. Operating Voltage : 3.3V
- *5. Backlight Supply : 175mA (9.3V(Typ.))
- *6. Backlight : White LED
- *7. Interface : RGB 24bits
- *8. Matching Connection : IMSA-11501S-40A-GFN1<IRISD>
- *9. Operating Temperature : -30°C~85°C
- *10. Storage Temperature : -40°C~90°C

C		
B		
A		
Rev	Note	Date
Dwg	Title	
Dwg No.	MK-007333-1-1	Date
Scale	1/1	2021-07-26
Tol.	±0.3	
Unit	mm	
Paper Size	A3	
Approved	Checked	Drawn
		Qiu Shaoping
TOPWAY		