



Note:

- *1. LCD Display Type: TFT,Transmissive(Full view)
- *2. Pixel Arrangement: RGB-STRIPE
- *3. Color Depth : 16.7M/262k Colors
- *4. Interface: LVDS(VESA 24bit Or 18bit)
- *5. Terminal:
 CN1: JAE FI-SE20P-HFE-E3000 Or Equivalent
 CN2: JAE FI-S6P-HFE-E1500 Or Equivalent
 CN3: MOLEX 53261-0871 Or Equivalent
- *6. Operating Voltage : 3.3V
- *7. Backlight: White LEDs
- *8. Backlight Supply: 12.0V
- *9. Touch Panel Type: Capacitive Touch Panel
- *10. Operating Temperature : -20°C~70°C
- *11. Storage Temperature : -30°C~80°C
- *12. Unmarked Tolerance : ≤150,±0.3; >150,±0.5

CN2 Terminal	
1	VLED
2	VLED
3	VLSS
4	VLSS
5	LED_EN
6	LED_PWM

CN3 Terminal	
1	VDD1
2	D-
3	D+
4	VSS1
5	NC
6	NC
7	NC
8	NC

CN1 Terminal	
No	Pin Name
1	IND3+
2	IND3-
3	NC
4	SEL6/8
5	VSS
6	PINC+
7	NINC-
8	VSS
9	IND2+
10	IND2-
11	VSS
12	IND1+
13	IND1-
14	VSS
15	IND0+
16	IND0-
17	VSS
18	NC
19	VDD
20	VDD

D		
C		
B		
A		
Rev Note		Date
Dwg Title		
LMT101GNLFWA-NND Outline Dwg		
Dwg No.	MK-009112-1-1	Date
		2026-04-23
Scale	Tol.	Unit
4/5		mm
Approved	Checked	Paper Size
		A3
		Drawn
		Taoqingwen

TOPWAY